Serial No.: 10/716,840

Filed: November 18, 2003

Page : 2 of 14

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

<u>Listing of Claims</u>:

1. (currently amended) A method for searching for one or more logical elements in a hierarchical tree structure of an extended extensible markup language (XML) document conforming to a schema used for XML, comprising:

providing a representation of an extended markup languageXML document instance containing two or more logical elements, wherein at least one logical element is a parent node and at least one logical element is a child node in a hierarchical tree structure describing the representation;

receiving a query for logical elements satisfying an XPath expression; [[and]] searching in the hierarchical tree structure only nodes that potentially have child nodes satisfying the XPath expression; and

providing the logical elements satisfying the XPath expression.

- 2. (Original) The method of claim 1, including the further step of generating a collection of parent nodes that potentially have child nodes satisfying the XPath expression from a table relating a class of parent nodes and a class of child nodes, and wherein the table is used in the final searching step.
- 3. (currently amended) The method of claim 1, including the further step of generating a collection of parent nodes that potentially have child nodes satisfying the XPath expression from a table relating parent nodes and child nodes, and wherein the table is used in the final searching step.

Serial No.: 10/716,840

Filed: November 18, 2003

Page : 3 of 14

4. (original) The method of claim 2, wherein the table comprises entries containing hash representations of a class of parent nodes and a class of child nodes.

5. (original) The method of claim 3, wherein the table comprises entries containing hash representations of the parent nodes and child nodes.

- 6. (original) The method of claim 2, wherein the table comprises a listing of permitted classes of child nodes for each class of parent node.
- 7. (original) The method of claim 3, wherein the table comprises a listing of child nodes for each parent node.
- 8. (original) The method of claim 2, wherein the table comprises a listing of permitted classes of parent nodes for each class of child node.
- 9. (original) The method of claim 3, wherein table comprises a listing of permitted parent nodes for each child node.
- 10. (currently amended) The method of claim 1, further comprising:

receiving a rule set identifying allowable combinations between child nodes and parent nodes in a hierarchical document structure;

transforming the rule set into a table relating a class of parent nodes and a class of child nodes; and

using the table in the [[final]] searching step.

11. (currently amended) The method of claim 1, further comprising:

receiving a rule set identifying allowable combinations between child nodes and parent nodes in a hierarchical document structure;

transforming the rule set into a table relating parent nodes and child nodes; and using the table in the [[final]] searching step.

Serial No.: 10/716,840

Filed: November 18, 2003

Page : 4 of 14

12. (original) The method of claim 10, wherein:

the rule set includes one of: an XML schema, a DTD, and a RelaxNg schema.

13. (original) The method of claim 11, wherein:

the rule set includes one of: an XML schema, a DTD, and a RelaxNg schema.

- 14. (original) The method of claim 2, wherein the table includes a listing of a not-permitted class of child nodes for each class of parent node.
- 15. (original) The method of claim 3, wherein the table includes a listing of not-permitted child nodes for each parent node.
- 16. (original) The method of claim 2, wherein the table includes a listing of a not-permitted class of parent nodes for each class of child node.
- 17. (original) The method of claim 3, wherein the table includes a listing of a not-permitted parent nodes for each child node.
- 18. (original) The method of claim 1, further comprising the additional steps of:

receiving a rule set identifying non-allowable combinations between child nodes and parent nodes in a hierarchical document structure; and

transforming the rule set into a table relating a class of parent nodes and a class of child nodes.

19. (original) The method of claim 1, further comprising the additional steps of:

receiving a rule set identifying non-allowable combinations between child nodes and parent nodes in a hierarchical document structure; and

transforming the rule set into a table relating parent nodes and child nodes.

20. (currently amended) A computer program product, <u>tangibly encoded on a computer-readable</u> <u>medium</u>, for searching for one or more logical elements in a hierarchical tree structure of an <u>extended extensible</u> markup language (XML) document conforming to a schema used for XML,

Serial No.: 10/716,840

Filed: November 18, 2003

Page : 5 of 14

comprising instructions operable to cause a programmable processor to:

provide a representation of an extended markup languageXML document instance containing two or more logical elements, wherein at least one logical element is a parent node and at least one logical element is a child node in a hierarchical tree structure describing the representation;

receive a query for logical elements satisfying an XPath expression; [[and]] search in the hierarchical tree structure only nodes that potentially have child nodes satisfying the math expression; and

provide the logical elements satisfying the XPath expression.

- 21. (original) The computer program product of claim 20, wherein the instructions cause a programmable processor to generate a collection of parent nodes that potentially have child nodes satisfying the XPath expression from a table relating a class of parent nodes and a class of child nodes, and wherein the instructions cause the table to be used in the search.
- 22. (original) The computer program product of claim 20, wherein the instructions cause a programmable processor to generate a collection of parent nodes that potentially have child nodes satisfying the XPath expression from a table relating parent nodes and child nodes, and wherein the instructions cause the table to be used in the search.
- 23. (original) The computer program product of claim 21, wherein the table comprises entries containing hash representations of the class of parent nodes and class of child nodes.
- 24. (original) The computer program product of claim 22, wherein the table comprises entries containing hash representations of the parent nodes and child nodes.
- 25. (original) The computer program product of claim 22, wherein the table comprises a listing of a permitted class of child nodes for each class of parent node.
- 26. (original) The computer program product of claim 21, wherein the table comprises a listing of permitted child nodes for each parent node.

Serial No.: 10/716,840

Filed: November 18, 2003

Page : 6 of 14

27. (original) The computer program product of claim 21, wherein the table comprises a listing of a permitted class of parent nodes for each class of child node.

- 28. (original) The computer program product of claim 22, wherein the table comprises a listing of permitted parent nodes for each child node.
- 29. (currently amended) The computer program product of claim 20, further comprising instructions to:

receive a rule set identifying allowable combinations between a class of child nodes and a class of parent nodes in a hierarchical document structure;

transform the rule set into a table relating the class of parent nodes and the class of child nodes; and use the table in the [[final]] search.

30. (currently amended) The computer program product of claim 20, further comprising instructions to:

receive a rule set identifying allowable combinations between child nodes and parent nodes in a hierarchical document structure;

transform the rule set into a table relating parent nodes and child nodes; and use the table in the [[final]] search.

- 31. (original) The computer program product of claim 29, wherein: the rule set includes one of: an XML schema, a DTD, and a RelaxNg schema.
- 32. (original) The computer program product of claim 30, wherein: the rule set includes one of: an XML schema, a DTD, and a RelaxNg schema.
- 33. (original) The computer program product of claim 21, wherein the wherein the table includes a listing of a class of not-permitted child nodes for each class of parent node.
- 34. (original) The computer program product of claim 22, wherein the wherein the table includes a listing of not-permitted child nodes for each parent node.

Serial No.: 10/716,840

Filed: November 18, 2003

Page : 7 of 14

35. (canceled)

36. (canceled)

- 37. (original) The computer program product of claim 21, wherein the wherein the table includes a listing of a class of not-permitted parent nodes for each class of child node.
- 38. (original) The computer program product of claim 22, wherein the wherein the table includes a listing of not-permitted parent nodes for each child node.
- 39. (original) The computer program product of claim 20, further comprising instructions to:
 receive a rule set identifying non-allowable combinations between a class of child nodes
 and a class of parent nodes in a hierarchical document structure; and

transform the rule set into a table relating the class of parent nodes and the class of child nodes.

40. (original) The computer program product of claim 20, further comprising instructions to:
receive a rule set identifying non-allowable combinations between child nodes and parent
nodes in a hierarchical document structure; and

transform the rule set into a table relating parent nodes and child nodes.